

## Glove MagneX 538



**NANOFinish™**

EN 388:2016  
+A1:2018



4121 X



**TOWA**

<b>Description</b>	Seamless glove with nitrile foam coating
<b>Material</b>	Liner: Polyamide (15 gauge) Coating: double dipped nitrile foam, NanoFinish surface
<b>Application areas</b>	Mechanics, assembly, agriculture, construction, etc.
<b>Product advantages</b>	Nitrile foam coating with new, patented coating technology "NanoFinish", particularly good grip very good mechanical properties (abrasion), oil resistant food safe very good dexterity and well-known TOWA-shape
<b>Single packaging</b>	headercard
<b>Standards</b>	KAT II, EN ISO 21420:2020, EN 388:2016+A1:2018

### Certification:

Feature	Level	Range
Abrasion resistance	4	Min 0 / Max 4
Cut resistance (Coupe-Test)	1	Min 0 / Max 5
Tear resistance	2	Min 0 / Max 4
Puncture resistance	1	Min 0 / Max 4
Cut resistance (ISO 13997)	X	A-F (X=not tested)

Rating	Range (• - ●●●●)
Durability	●●●●
Dexterity	●●●●
Moisture protection	●●
Grease/Oil resistance	●●●●
Slip resistance	●●●●●
Breathability	●●●●

### Logistical Data:

Item no.	Size	Barcode	MOQ	Packaging Unit	Pal
297685	7 / S	4018653265895	1 Pair	1/6/144	1.440
297686	8 / M	4018653265901	1 Pair	1/6/144	1.440
297687	9 / L	4018653265918	1 Pair	1/6/144	1.440
297688	10 / XL	4018653265925	1 Pair	1/6/144	1.440
297689	11 / XXL	4018653265932	1 Pair	1/6/144	1.440