

Glove MagneX 538






**STANDARD
100**

N-KEN 12118
Nissenken

www.oeko-tex.com

Description	Seamless glove with nitrile foam coating
Material	Liner: Polyamide (15 gauge) Coating: double dipped nitrile foam, NanoFinish surface
Application areas	Mechanics, assembly, agriculture, construction, etc.
Product advantages	Nitrile foam coating with new, patented coating technology "NanoFinish", particularly good grip very good mechanical properties (abrasion), oil resistant food safe very good dexterity and well-known TOWA-shape
Single packaging	headercard
Standards	KAT II, EN ISO 21420:2020, EN 388:2016+A1:2018

Certification:

Feature	Level	Range
Abrasion resistance	4	Min 0 / Max 4
Cut resistance (Coupe-Test)	1	Min 0 / Max 5
Tear resistance	2	Min 0 / Max 4
Puncture resistance	1	Min 0 / Max 4
Cut resistance (ISO 13997)	X	A-F (X=not tested)

Rating	Range (• - ●●●●)
Durability	●●●●
Dexterity	●●●●
Moisture protection	●●
Grease/Oil resistance	●●●●
Slip resistance	●●●●●
Breathability	●●●●

Logistical Data:

Item no.	Size	Barcode	MOQ	Packaging Unit	Pal
297685	7 / S	4018653265895	1 Pair	1/6/144	1.440
297686	8 / M	4018653265901	1 Pair	1/6/144	1.440
297687	9 / L	4018653265918	1 Pair	1/6/144	1.440
297688	10 / XL	4018653265925	1 Pair	1/6/144	1.440
297689	11 / XXL	4018653265932	1 Pair	1/6/144	1.440